Near-real-time Satellite Cloud Products For Icing Detection And Aviation Weather Over The USA

Patrick Minnis, William L. Smith, Jr., Louis Nguyen

Atmospheric Sciences

NASA Langley Research Center, Hampton, VA

Patrick Heck, Mandy Khaiyer, Douglas A. Spangenberg AS&M, Inc., Hampton, VA



Acknowledgements

• John Murray, ASAP/AVSP NASA LaRC

• B. Bernstein, F. McDonough, NCAR/ RAP, Boulder CO

• Tom Ratvasky and NASA Glenn Twin Otter Icing Team



OBJECTIVES

• Develop a satellite-based icing detection methodology that can be applied operationally with results provided in a timely manner as part of an integrated icing product for the aviation community

• The satellite data to provide near-real time cloud-top & base altitudes for aviation weather applications



OUTLINE

• DESCRIPTION OF METHODOLOGY AND CLOUD PRODUCTS

•RELATING AIRCRAFT ICING TO SATELLITE CLOUD PARAMETERS

SATELLITE FIELD SUPPORT

• DEMONSTRATION OF PROTOTYPE PRODUCT



APPROACH

- Use cloud properties currently being derived from satellite data at various time and space scales and relate them to aircraft icing
 - -Developed & applied algorithms to various satellite (GOES, AVHRR, etc.) data for field programs for climate research
 - Currently deriving global cloud and radiation parameters from EOS sensors for global change studies as part of the Clouds and Earth's Radiant Energy System (CERES) Experiment post processing
 - Applying similar algorithms to 4-km GOES data to derive cloud and radiation parameters for DOE ARM program over SGP, for NASA CRYSTAL(FL), Icing (Midwest) running experimentally in R/T



PIXEL-LEVEL CLOUD PROPERTIES

EFFECTIVE RADIATING TEMP Tc **EFFECTIVE HEIGHT, PRESSURE** Zc, pc **TOP PRESSURE, HEIGHT p**₊, **z**₊ **THICKNESS** h **EMISSIVITY** PHASE (water or ice; 1 or 2) P WATER DROPLET EFFECTIVE RADIUS re **OPTICAL DEPTH** LIQUID WATER PATH **LWP** ICE EFFECTIVE DIAMETER De **ICE WATER PATH IWP**

Blue indicates utility for icing



ICING

ICING CONDITIONS ARE DETERMINED BY CLOUD

liquid water content, LWC

• temperature, T(z)

• droplet size distribution, N(r)

positive w/ intensity

negative w/ intensity

r positive w/ intensity

SATELLITE REMOTE SENSING CAN DETERMINE CLOUD

- optical depth, []
- effective droplet size, re
- liquid water path, LWP
- cloud top temperature, Tc
- thickness, h

IN CERTAIN CIRCUMSTANCES



CLOUD PRODUCTS VS. ICING PARAMETERS

•
$$LWP = LWC * h$$

•
$$re = f[N(r)]$$

- Tc & h can yield depth of freezing layer
- z_t is top of icing layer
- ceiling = z_t h

IN MANY CASES, SATELLITE REMOTE SENSING SHOULD PROVIDE ICING INFORMATION



DATA

- GOES-8 IMAGER (4KM RESOLUTION) 75° W

Visible $(0.63 \mu m; ch.1)$ Solar Infrared $(3.9 \mu m; ch.2)$ IR Window $(10.8 \mu m; ch.4)$

Split Window (12.0 μ m; ch.5) (G-12: 13.3 μ m)

Visible Channel Calibrated Following Minnis et al. 2002

- Rapid Update Cycle (RUC) 20 km x 20 km hourly analyses
 - surface air temperature => skin temperature
 - temperature & moisture profiles => absorption correction, heights
- CERES clear-sky albedo, surface emissivity (10', 1°)


clear-sky reflectance, brightness temperature => cloud detection/retrieval

- Theoretical cloud reflectance & emittance models

describes angular variation for range of re and $\square =>$ cloud detection/retrieval



METHODOLOGY FOR EACH IMAGE TIME





CLOUD MASK

- To detect clouds, the radiances for cloud-free (clear) scene must be known
- Determine clear-sky albedos and surface emissivities after initial processing of data
 - start with CERES values and update
- Use RUC surface temperatures & profiles to estimate clear-sky brightness temperatures
- Must account for angular dependence: bidirectional reflectance models to estimate clear-sky reflectance for each pixel
- Estimate thresholds based on uncertainties in models & spatial/temporal variability of the clear radiances



CLEAR-SKY RADIANCE CHARACTERIZATION

- Predict radiance a given satellite sensor would measure for each channel if no clouds are present
- Estimate uncertainty based on spatial & temporal variability
 & angular model errors
- Develop set of spectral thresholds for each channel
 - Solar, uses reflectance, □
 - IR, use temperature, T

brightness temperature difference, BTD = $T_{\square 1}$ - $T_{\square 2}$ typically, BTD(3.7-11) or BTD(11-12)




CLEAR-SKY REFLECTANCE, SOLAR

- Estimate overhead-sun albedo, $\Box_o = \Box(\mu_o = 1)$ derived empirically with initial runs using CERES VIRS data, then updated for each month using GOES
- Estimate albedo at given local time, $\square(\mu_o) = \square_o \square_o(\mu_o)$ directional reflectance model $\square_o(\mu_o)$ derived for each IGBP type using VIRS
- Estimate reflectance for given viewing angles, $[(\mu_o, \mu, [)] = [(\mu_o)] [(\mu_o, \mu, [)]]$ bidirectional reflectance (BRDF) model [] selected for each surface type from Kriebel (1978), Minnis & Harrison (1984), Suttles et al. (1988)
- Add uncertainty to set reflectance threshold, $\Box_T(\mu_o, \mu, \Box) = \Box + \Box\Box(\mu_o, \mu, \Box)$



PREDICTED CLEAR-SKY & OBSERVED VIS REFLECTANCE & CLOUD MASK 1700 UTC,12/21/00



CLEAR-SKY TEMPERATURE, INFRARED


Estimate surface emissivity, □_s(x,y)

derived empirically with using ISCCP AVHRR DX, VIRS, then Terra MODIS; water & snow theoretical models


- Estimate radiance leaving the surface, $L_s = \Box_s B(T_{skin}) + (1-\Box_s) L_{ad}$ $L_{ad} = downwelling \ atmo \ radiation, \ T_{skin} = skin \ temperature \ from \ model \ / \ obs$
- Estimate TOA brightness temperature, $B(T_{cs}) = (1-\Box_a)L_s + \Box_a L_{au}$ $L_{au} = upwelling \ atmo \ radiation, \ \Box_a = effective \ emissivity \ of \ atmo$ $layer \ absorption \ emission \ computed \ using \ T/RH \ profile, \ correlated \ k-dist$
- Add uncertainty to set T or BTD thresholds, $T_T(\mu) = T_{cs}(\mu) + \Box T(\mu)$
 - reflected solar component included in 3.7-4.0 μm estimate



PREDICTED CLEAR-SKY & OBSERVED IR TEMPERATURE 1700 UTC,12/21/00





PREDICTED CLEAR-SKY & OBSERVED BTD (3.7 - 11) 1700 UTC,12/21/00




STANDARD DAYTIME MASK ALGORITHM

Top Level Daytime Flow Chart






CERES CLOUD MASK 1700 UTC,12/21/00




STANDARD NIGHTTIME MASK ALGORITHM

Top Level Nighttime Flow Chart



CERES CLOUD MASK & BTD(3.7 - 11) REFLECTANCE 0400 UTC,12/01/00



DAYTIME CLOUD RETRIEVALS

- •VISST (Visible, infrared, solar-infrared, split-window technique)
 - physically based method using 0.65, 3.7, 11, & 12 μ m
 - for cloudy pixels, match radiances to model values
- Yields more accurate cloud temperatures than simpler methods
 - adjusts temperature (altitude) of thin clouds
- Provides basis for determining phase
 - in most cases, ice & water models are distinct



Daytime Cloud Property Retrievals

- Derive cloud properties by matching observed radiances to model calculations for water droplets ($2 < r_e < 32 \text{ [m)}$) and ice crystals ($6 < D_e < 135 \text{ [m)}$) through reflectance and emittance parameterizations
- 3.9 ☐m (GOES Channel 2) used for particle size retrieval
- Particle phase determined by:
 - (1) Best available model solution
- (2) $T_{10.8}$ $T_{12.0}$ Difference
- (3) Visible/IR Layer Retrieval
- (4) Retrieved Cloud Temperature




Cloud Tau, phase, r_e (D_e), LWP (IWP), Z_{cld} , T_{cld}




Cloud properties from GOES-8

1815 UTC









Cloud mask & optical depths from GOES-8

1815 UTC









Cloud droplet radius & LWP from GOES-8

1815 UTC








Cloud-top temperature & height from GOES-8


1815 UTC





ARM-Sponsored Comparisons (March 2000)

Comparison of Surface, GOES and Aircraft Results (~10 hours)






Comparison of Optical Depths (OD) from VISST & SINT, Terra MODIS

Northern Alaska March 3, 2001 2100 UTC

Visible channel overestimates OD over snow & ice

1.6-µm yields more cealistic value for OD 80





Comparison of Super-Cooled Liquid Water Cloud Properties Derived from Satellite and Aircraft Measurements




Validation of Satellite-Derived SLW Cloud Properties

How do satellite retrievals of Tcld, Re, LWP correspond to aircraft icing?

- •Correlate with measurements from icing research aircraft (NASA GRC)
 - Winter 1998 NASA/FAA/NCAR Supercooled Large Droplet Research Project and compare satellite retrievals with:
- Correlate with PIREPS
 - 1998 Flight days
 - Jan 15 Mar 30, 2003 (real-time runs to support Twin Otter flights)


GOES detects SLW for all 46 Twin Otter SLW cloud top penetrations (McDonough and Bernstein, 2000)





x - denotes Twin Otter cloud top penetrations


GOES detects SLW for all 46 Twin Otter SLW cloud top penetrations (McDonough and Bernstein, 2000)















x - denotes Twin Otter cloud top penetrations


GOES SLW vs. PIREPS Icing

Compared to Positive icing PIREPS and provided there were no overcast ice clouds, LaRC GOES technique detected SLW 98% of the time (Smith et al., 2000)


Comparison of GOES Cloud Properties with PIREPS Icing Intensity N=7800 (Jan-March, 2003)



GOES-Derived Cloud Properties (Dec. 9, 1997)




PIREP Icing Intensity at 16-18 UTC Dec. 9, 1997




PIREP Icing Intensity at 19-21 UTC Dec. 9, 1997




GOES-Derived Cloud Properties (March 5, 1998)




PIREP Icing Intensity at 17-19 UTC Mar. 5, 1998




GOES Water Droplet Radius




GOES Droplet Radius




GOES Liquid Water Path



Satellite/Aircraft Comparison March 5, 1998




Satellite/Aircraft Comparison March 5, 1998




PROTOTYPE ICING CATEGORIES


<u>value</u>	<u>Criteria</u>			icing intensity
0	clear or water clo			
		ice cloud w/OD <	no ice	
1	ice cloud	optical depth > 8.	indeterminate	
2	re > 11 μm	LWP > 100	Tcld < 272 K	low
3	$re > 11 \mu m$	LWP > 200	Tcld < 272 K	mid
4	$re > 11 \mu m$	LWP > 300	Tcld < 272 K	high
5	$re > 9 \mu m$	LWP > 400	Tcld < 272 K	low
6	$re > 9 \mu m$	LWP > 500	Tcld < 272 K	mid
7	$re > 11 \mu m$	LWP > 300	Tcld < 253 K	high
8	$re > 9 \mu m$	LWP > 400,	Tcld < 253 K	high

GOES ICING







GOES Droplet Radius





GOES LWP




GOES ICING













Evelyth, Minn. King Air Crash Oct 25, 2002 at 1645 UTC













Evelyth, Minn. King Air Crash Oct 25, 2002 at 1645 UTC










Cloud Height Comparisons 1997-98 Twin Otter Icing Flights vs GOES Lapse Rate Method

ztopcld = estimated height of all cloud in view

zeffliq = estimated height of liquid clouds only






WEB-BASED SATELLITE SUPPORT FOR FIELD PROGRAMS

- Evolving web page satellite product, forecast support for field programs
 - history starting with NASA FIRE experiments
 - real time imagery in ARM field experiments
 - satellite overpass & viewing conditions in INCA (2001)
 - real time satellite imagery, cloud products, etc. in CRYSTAL-FACE 2002
 - supported THORPEX and will support again this fall
- Real time satellite ingests via MCIDA, archived& gifs on web (other sats when req'd)
 - GOES E/W
 - AVHRR
 - Terra/Aqua MODIS
- Real time model reanalyses/forecasts & surface data via MCIDAS



COMBINING GOES-EAST & WEST FOR CONUS DOMAIN

Proposed domain: 25°N - 50°N; 50°W - 130°W





EXPANSION PROCESS


- Focus on GOES-East (50°W 105°W)
 - Develop ingest system for model & satellite input
 - Size the problem for computer processing
 - Provide products online (graphical & digital)
 - Make alterations for new channel (13.5 μ m)
- Focus on GOES-West (105°W 135°W)
 - Intercalibrate east & west
 - Develop ingest system
 - Combine results with East for seamless product



Initial Clear-sky Visible (0.65 μ m) Albedos for CONUS Cloud Analysis

Overhead Sun Values
Derived From 1998
VIRS Data by CERES
Project

GOES Visible Channels Have Slightly Different Wavelengths Requiring Refinement for Future GOES Applications






Initial 3.7- μ m Surface Emissivities for CONUS Cloud Analysis


Derived From AVHRR Data by CERES Project

GOES Solar Infrared Channel Has Different Wavelength (3.9 µm) Requiring Refinement for Future GOES Applications






Combined GOES-8 & GOES-10 CONUS Imagery Visible Channel, 28 January 2003, 1745 UTC




Combined GOES-8 & GOES-10 CONUS Cloud Mask

28 January 2003, 1745 UTC




Combined GOES-8 & GOES-10 CONUS Cloud Temperature

28 January 2003, 1745 UTC




Combined GOES-8 & GOES-10 CONUS Cloud Top Altitude

28 January 2003, 1745 UTC



Combined GOES-8 & GOES-10 CONUS Cloud Base Altitude

28 January 2003, 1745 UTC




PROTOTYPE ICING CATEGORIES

<u>value</u>	<u>Criteria</u>			icing intensity
0	clear or water clo	oud (w/Tcld > 272 I ice cloud w/OD <	no ice	
1	ice cloud	optical depth > 8	.0	indeterminate
2	$re > 11 \mu m$	LWP > 100	Tcld < 272 K	low
3	$re > 11 \mu m$	LWP > 200	Tcld < 272 K	mid
4	$re > 11 \mu m$	LWP > 300	Tcld < 272 K	high
5	$re > 9 \mu m$	LWP > 400	Tcld < 272 K	low
6	$re > 9 \mu m$	LWP > 500	Tcld < 272 K	mid
7	$re > 11 \mu m$	LWP > 300	Tcld < 253 K	high
8	$re > 9 \mu m$	LWP > 400,	Tcld < 253 K	high



Combined GOES-8 & GOES-10 CONUS Icing Category PROTOTYPE


28 January 2003, 1745 UTC






Combined GOES-8 & GOES-10 CONUS Icing Probability PROTOTYPE

28 January 2003, 1745 UTC






Comparison of Icing Categories With PIREPS, 9 Dec 1997, 1545 UTC






Comparison of Icing Categories With PIREPS, 9 Dec 1997, 1645 UTC






Comparison of Icing Categories With PIREPS, 9 Dec 1997, 1745 UTC





Comparison of Icing Categories With PIREPS, 9 Dec 1997, 1932 UTC






Comparison of Icing Categories With PIREPS, 9 Dec 1997, 2032 UTC

PIREP Icing generally corresponds to yellow (high):

LWP > 300 g/m² & re > 11 μ m





SUMMARY

- Prototype system has been developed to produce icing products over CONUS every 15-30 minutes during daytime
 - icing intensity
 - cloud-top & base heights
- ☐ nitial validations appear promising
 - Much additional aircraft, radar, and model verification needed AIRS and other future & previous experiments




CHALLENGES TO BE ADDRESSED

- Icing definition (probability, intensity)
 - objective definition, relate satellite parameters to icing
- •Daytime validation, algorithm refinement
 - aircraft & surface measurements, cirrus contamination, input maps, backscatter angle bias, snow background (1.6/3.7 μ m), impact of size distribution on retrieval, cloud height/base/vertical slicing
- Multilayer / high-cloud
 - what inferences can be made in obscured conditions?
- Dighttime/twilight algorithm refinement
 - how far can we push infrared techniques?
- Se of microwave data (DMSP, TRMM, AMSR) for ocean (single and multilayer)
- Integration of satellite results into comprehensive, operational icing product




COMPARISON OF IN SITU & MWR (Lin) LWP, FIRE ACE 2000

Can apply microwave method over ocean to retrieve LWP & Tcld in both obscured (ice cloud) & unobscured conditions (DMSP, AMSR data)



Nighttime Analyses over Central USA March 5, 2003





LINKS

- Main homepage: www-pm.larc.nasa.gov
- R/T Imagery: www-angler.larc.nasa.gov/armsgp/g8usa.html
- R/T Products
 - ARM SGP: www-angler.larc.nasa.gov/armsgp/cldprod4.html
 - Midwest USA: www-angler.larc.nasa.gov/armsgp/ cldprod4ohio.html
 - Florida: www-angler.larc.nasa.gov/crystal/ cldprod4.html
 - CONUS Icing: under development, prelim results on main homepage-Icing link
 - Patrick Minnis: p.minnis@nasa.gov
 - Bill Smith: william.l.smith@nasa.gov

